

BAT 100 LSN Display Panel

www.boschsecurity.com



BOSCH
Invented for life




- ▶ Upgradeable with up to three ATG 420 LSNi kits
- ▶ 32, 64 or 96 multicolor display LEDs
- ▶ Monitored data communication control panel - display panel
- ▶ Maintenance of function on the LSN loop via two integrated isolators in the event of wire interruptions or short-circuits

The BAT 100 LSN Display Panel is a universally usable remote parallel display with up to 96 LEDs (e.g. for a maximum of 96 detector zones).

- 3 Keys for "LED test" or "buzzer off"
- 4 Tamper contact

System overview



Item	Description
	BAT 100 LSN, display without hood
1	Lower part of housing
2	ATG with 32 LEDs

Functions

The BAT 100 LSN Display Panel handles the display of faults and/or alarms for detectors or detector zones. Up to three ATG 420 LSNi kits can be installed in the BAT 100 LSN housing. An ATG 420 LSNi includes 32 red LEDs for alarm indications or 32 yellow LEDs for fault indications. Mixed equipment (red and yellow LEDs) of the display panel with different ATG 420 LSNi is possible.

LED displays can be labeled using a printer. The panel has a buzzer and a reset button for the buzzer. If there is no alarm, the reset button for the LED test can be used.

The ATG 420 LSNi kits have integrated isolators for maintaining the function of the elements on the LSN loop in the event of wire interruptions or short-circuits.

Certifications and approvals

- ATG 420 LSNi and ATB 420 LSNi complied
- EN54-17:2005


- EN54-18:2005

Region	Certification	
Europe	CPR	0786-CPR-21484 BAT 100 LSN
Germany	VdS	G 216008 BAT 100 LSN

Installation/configuration notes

- BAT 100 LSN Display Panels can be incorporated at any point on LSN loops or LSN stubs.

Planning example



Parts included

Qty.	Component
1	BAT 100 LSN Display Panel
1	ATG 420 LSNi Display Module

Technical specifications

Electrics

ATG 420 LSNi module

Operating voltage	
<ul style="list-style-type: none"> LSN part other functions 	<ul style="list-style-type: none"> +15 V DC to +33 V DC +8 V DC to +30 V DC
Current consumption	
<ul style="list-style-type: none"> LSN part other functions 	<ul style="list-style-type: none"> 3 mA - all 32 LEDs off: max. 10 mA@ 24 V DC or max. 15 mA@ 8 V DC - all 32 LEDs on: max. 25 mA@ 24 V DC or max. 60 mA@ 8 V DC

Mechanics

BAT 100 LSN housing

Dimensions (H x W x D)	270 x 270 x 75 mm
Material	Plastic, ABS Terluran
Color	Light gray, RAL 9002
Weight	Approx. 1 kg

Environmental conditions

Permissible operating temperature	-5 °C to +50 °C
Permissible storage temperature	-20 °C to +60 °C

Special features

LED flash frequency	1.25 Hz
LED colors	Multicolor

Ordering information

BAT 100 LSN Display Panel

Universally-usable remote parallel display with up to 96 LEDs

Order number **BAT 100**

Accessories

Labeling Strips

PU = 10 units

Order number **BAT100-LABELS**

Represented by:

North America:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
203 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

Latin America and Caribbean:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com